

Hammer-In Drywall Anchors

Instructions

For hanging items on 1/2" and 5/8" drywall. Same anchor works in BOTH 1/2" and 5/8" drywall. For kitchen, bath, art, shelving, closet, curtains, towel bars, and many other fixtures.



HAMMER – FASTEN – DONE

DEMO: <http://www.wallclaw.com/loc-n-load-demo-video/>

1. Hold the top and bottom of anchor body between your thumb and index finger.
2. Be sure the arrow on the top of the HEAD of the anchor is pointed up. See image →
3. Place the pointed nail tip of anchor on the wall where installation is desired.
4. Gently, and repeatedly tap the head of the anchor and gently drive the anchor into the wall.
5. Do NOT countersink the head into the drywall – this can damage the drywall.
6. Maximum thickness of fixture (bracket, mounting plate, etc.) should not exceed 1/8-inch with the 1-1/4" screw provided.
7. If fixture is thicker than 1/8-inch obtain a longer #8 Type B (Blunt Tip) screw similar to those provided with the anchor.
8. Attach fixture to anchor using BLUNT tip screws provided. Do NOT use sharp tipped screws.
9. When the screw is inserted and activates the locking leg behind the wall, the anchor head will draw flush onto the wall.



REMOVAL

1. Back screw out of anchor and remove fixture.
2. Removal of screw releases locking leg behind wall.
3. Reinsert screw into anchor – ONLY 1/4-inch.
4. Use screw as a handle and gently pull back on the screw, gently wiggle anchor and as anchor comes out pull back and lift.
5. The small slit left behind in the wall is easily patched, typically with one pass of spackle.

Maximum hanging load may vary, based on the quality and thickness of drywall, drywall condition, dimensions of object being hung and distance of object off face of wall. Other variables may also apply.

Not intended for use in studs or for ceiling applications.

Limited Warranty. These products are sold 'AS IS' without any expressed or implied warranties. WallClaw Anchor's sole liability, if any, shall be to replace this product or refund the purchase price. The performance of these products is subject to variable conditions.

WallClaw®, LOC-N-LOAD®, Blade®, Crystal® & Rocket® Anchors are registered trademarks. Patent, Trademark and Copyright Protected.

90 LBS <hr/> 1/2" WALL includes safety factor	125 LBS <hr/> 5/8" WALL includes safety factor
 No Drilling No Mess	 Small Slit Left Easy Repair